




1 Identification of the substance/mixture and of the company/undertaking

- **Product details**
- **Trade name:** Dinitrol 6080 Fiberplast Spachtel
- **Application of the substance / the preparation** Knife filler/ Surfacer
- **Manufacturer/Supplier:**
Dinol GmbH
Pyrmonter Strasse 76
D-32676 Lügde
Tel: +49 5281 9829 80
Fax: +49 5281 9829 860
E-mail: thomas.suerig@dinol.com
- **Further information obtainable from:** Research & Development
- **Information in case of emergency:** Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
 Xn; Harmful
 R20: Harmful by inhalation.
-  Xi; Irritant
 R36/38: Irritating to eyes and skin.
- R10: Flammable.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
 Xn Harmful
- **Hazard-determining components of labelling:**
Styrene
- **Risk phrases:**
10 Flammable.
20 Harmful by inhalation.
36/38 Irritating to eyes and skin.
- **Safety phrases:**
2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
13 Keep away from food, drink and animal feedingstuffs.

(Contd. on page 2)

Trade name: Dinitrol 6080 Fiberplast Spachtel

(Contd. of page 1)

23 Do not breathe fumes/aerosol.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

3 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 100-42-5	Styrene	☒ Xn R20; ☒ Xi R36/38	10-25%
EINECS: 202-851-5		R10	

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Firefighting measures

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

· **Special hazards caused by the substance, its products of combustion or resulting gases:** Carbon monoxide (CO)

· **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

· **Person-related safety precautions:**

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Trade name: Dinitrol 6080 Fiberplast Spachtel

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

100-42-5 Styrene

WEL	Short-term value: 1080 mg/m ³ , 250 ppm
	Long-term value: 430 mg/m ³ , 100 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

- **Material of gloves**
Neoprene gloves (0,47 mm)
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Not suitable are gloves made of the following materials:** Natural rubber

(Contd. on page 4)

Trade name: Dinitrol 6080 Fiberplast Spachtel

(Contd. of page 3)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form: Pasty
Colour: Light green
Odour: Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 145°C

· **Flash point:** 31°C

· **Ignition temperature:** 480°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %
Upper: 8.9 Vol %

· **Vapour pressure At 20°C:** 6 hPa

· **Density At 20°C:** 1.24 g/cm³

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents: 22.0 %

· **Additional information:**

VOC (EU): 24.00 %
VOC (EU): 250.0 g/l

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Materials to be avoided:**

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 5)

Trade name: Dinitrol 6080 Fiberplast Spachtel

(Contd. of page 4)

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

100-42-5 Styrene

Oral	LD50	5000 mg/kg (rat)
Inhalative	LC50/4h	24 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

· **Inhalation:** Harmful by inhalation.

12 Ecological information

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 11	adhesive and sealant sludges containing organic solvents or other dangerous substances

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 6)

Trade name: **Dinitrol 6080 Fiberplast Spachtel**

(Contd. of page 5)

14 Transport information

· **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 39
- **UN-Number:** 3269
- **Packaging group:** III
- **Hazard label** 3
- **Description of goods:** 3269 POLYESTER RESIN KIT, mixture
- **Limited quantities (LQ)** LQ7
- **Transport category** 3
- **Tunnel restriction code** E

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 3269
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-D
- **Marine pollutant:** No
- **Proper shipping name:** POLYESTER RESIN KIT, mixture

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 3269
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** POLYESTER RESIN KIT, mixture

15 Regulatory information

- **Chemical safety assessment** A Chemical Safety Assessment has not been carried out.
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
NK	10-25

(Contd. on page 7)

Printing date 07.10.2010

Revision: 07.10.2010

Trade name: Dinitrol 6080 Fiberplast Spachtel

(Contd. of page 6)

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

R10 Flammable.

R20 Harmful by inhalation.

R36/38 Irritating to eyes and skin.

· **Department issuing MSDS:** Research & Development· **Contact:** Dr. Thomas Sürig· *** Data compared to the previous version altered.**

GB