

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** Dinitrol 6110 Megafill
- **Application of the substance / the preparation** Priming
- **Manufacturer/Supplier:** EFTEC Aftermarket GmbH Pyrmonterstr. 76 D-32676 Lügde
- **Further information obtainable from:**
 Tel. +49(0)5281 98298 0, FAX +49(0)5281 98298 60
 Hans.Pfau@eftec.de
- **Information in case of emergency:** +49(0)30 19240 Beratungsstelle für Vergiftungserscheinungen, D-Berlin





2 Hazards identification

- **Hazard description:**
 Xi Irritant
 F+ Extremely flammable
- **Information concerning particular hazards for human and environment:**
 The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
 Warning! Pressurized container.
 Has a narcotizing effect.
 R 12 Extremely flammable.
 R 36 Irritating to eyes.
 R 67 Vapours may cause drowsiness and dizziness.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
 Buildup of explosive mixtures possible without sufficient ventilation.
 Keep out of the reach of children
- **Classification system:**
 The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7	butane	 F+; R 12	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane	 F+; R 12	10-25%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate	 Xi,  F; R 11-36-66-67	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate	R 10-66-67	10-25%

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: Dinitrol 6110 Megafill

(Contd. of page 1)

CAS: 67-64-1 EINECS: 200-662-2	acetone	Xi, F; R 11-36-66-67	10-25%
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one	Xn, Xi, F; R 11-20-36/37-66	5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene, mixture of isomers	Xn, Xi; R 10-20/21-38	5-10%
	cellulose nitrate	E; R 3	1-5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **Information for doctor:**
- **The following symptoms may occur:**
Headache
Dizziness
Dizziness
- **Treatment** If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Special hazards caused by the substance, its products of combustion or resulting gases:**
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Person-related safety precautions:**
Ensure adequate ventilation
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Additional information:** See Section 13 for disposal information.

GB

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: **Dinitrol 6110 Megafill**

(Contd. of page 2)

7 Handling and storage

- **Handling:**

- **Information for safe handling:**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- **Maximum storage temperature:** < 50 °C

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

108-10-1 4-methylpentan-2-one

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
Sk	

(Contd. on page 4)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: **Dinitrol 6110 Megafill**

(Contd. of page 3)

1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:** Not required.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**
Nitrile rubber, NBR
- **For the permanent contact gloves made of the following materials are suitable:** Nitrile rubber, NBR
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Nitrile rubber, NBR
Neoprene gloves
- **As protection from splashes gloves made of the following materials are suitable:**
Nitrile rubber, NBR
Neoprene gloves
- **Not suitable are gloves made of the following materials:** Strong material gloves
- **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

· General Information

Form:	Aerosol
Colour:	Light grey
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 5)

-GB

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: **Dinitrol 6110 Megafill**

(Contd. of page 4)

Boiling point/Boiling range:	< 35°C
· Flash point:	-97°C
· Ignition temperature:	365°C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20°C:	3600 hPa
· Density at 20°C:	0.82 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	74.9 %
· Solids content:	24.5 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

GB

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: **Dinitrol 6110 Megafill**

(Contd. of page 5)

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04	gases in pressure containers (including halons) containing dangerous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10	packaging containing residues of or contaminated by dangerous substances

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 2 5F Gases.

· **Danger code (Kemler):** -

· **UN-Number:** 1950

· **Packaging group:** -

· **Hazard label** 2.1

· **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



· **IMDG Class:** 2.1

· **UN Number:** 1950

· **Label** 2.1

· **Packaging group:** -

· **EMS Number:** F-D,S-U

· **Marine pollutant:** No

(Contd. on page 7)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: **Dinitrol 6110 Megafill**

(Contd. of page 6)

· **Proper shipping name:** AEROSOLS· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 2.1
 · **UN/ID Number:** 1950
 · **Label:** 2.1
 · **Packaging group:** -
 · **Proper shipping name:** AEROSOLS, flammable

* 15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant
 F+ Extremely flammable

· **Risk phrases:**

12 Extremely flammable.
 36 Irritating to eyes.
 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

3 Keep in a cool place.
 9 Keep container in a well-ventilated place.
 16 Keep away from sources of ignition - No smoking.
 23 Do not breathe fumes/aerosol.
 51 Use only in well-ventilated areas.
 60 This material and its container must be disposed of as hazardous waste.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
 Buildup of explosive mixtures possible without sufficient ventilation.
 Keep out of the reach of children

· **National regulations:**

141-78-6	ethyl acetate
1330-20-7	xylene, mixture of isomers

· **Technical instructions (air):**

Class	Share in %
NK	50-100

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2009

Revision: 24.03.2009

Trade name: Dinitrol 6110 Megafill

(Contd. of page 7)

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **EU-VOC:** 75.50 %

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20 Harmful by inhalation.
- 20/21 Harmful by inhalation and in contact with skin.
- 3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.
- 36 Irritating to eyes.
- 36/37 Irritating to eyes and respiratory system.
- 38 Irritating to skin.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** Entwicklung
- **Contact:** H. Pfau
- *** Data compared to the previous version altered.**