

1 Identification of the substance/mixture and of the company/undertaking

· **Product details**

· **Trade name:** Dinitrol 8500 Lackgrundierer Grau AC Spray

· **Application of the substance / the preparation** Priming

· **Manufacturer/Supplier:**

Dinol GmbH

Pyrmonter Strasse 76

D-32676 Lügde

Tel: +49 5281 9829 80

Fax: +49 5281 9829 860

E-mail: thomas.suerig@dinol.com

· **Further information obtainable from:** Research & Development

· **Information in case of emergency:** Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20: Harmful by inhalation.



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful

F+ Extremely flammable

· **Risk phrases:**

12 Extremely flammable.

20 Harmful by inhalation.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 1)

· **Safety phrases:**

- 2 Keep out of the reach of children.
 16 Keep away from sources of ignition - No smoking.
 23 Do not breathe fumes/aerosol.
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
 46 If swallowed, seek medical advice immediately and show this container or label.
 51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.
















· **Classification in accordance with Directive 75/324/EEC: Extremely flammable**

3 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	Acetone	 Xi R36;  F R11 R66-67	10-<25%
CAS: 74-98-6 EINECS: 200-827-9	Propane liquefied	 F+ R12	10-<25%
CAS: 106-97-8 EINECS: 203-448-7	Butane, pure	 F+ R12	10-<25%
CAS: 108-10-1 EINECS: 203-550-1	4-Methylpentan-2-one	 Xn R20;  Xi R36/37;  F R11 R66	10-<25%
CAS: 141-78-6 EINECS: 205-500-4	Ethyl acetate	 Xi R36;  F R11 R66-67	10-<25%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene, mixed isomers, pure	 Xn R20/21;  Xi R38 R10	5-<10%
CAS: 123-86-4 EINECS: 204-658-1	n-Butyl acetate	R10-66-67	1-<5%
CAS: 9004-70-0	Cellulose nitrate	 F R11	1-<5%
CAS: 71-76-3 EINECS: 200-751-6	n-Butanol	 Xn R22;  Xi R37/38-41 R10-67	1-<5%
CAS: 7779-90-0 EINECS: 231-944-3	Trizinc bis(orthophosphate)	 N R50/53	<1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.*
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- **The following symptoms may occur:**
Headache
Dizziness

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 3)

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 Acetone (10-<25%)

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

106-97-8 Butane, pure (10-<25%)

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

108-10-1 4-Methylpentan-2-one (10-<25%)

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk
-----	--

141-78-6 Ethyl acetate (10-<25%)

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

1330-20-7 Xylene, mixed isomers, pure (5-<10%)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

123-86-4 n-Butyl acetate (1-<5%)

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:** Protective gloves and protective skin cream

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:** Strong material gloves

(Contd. on page 5)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Grey

· **Odour:** Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** < -20°C

· **Ignition temperature:** 365°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.5 Vol %

Upper: 13.0 Vol %

· **Vapour pressure At 20°C:** 3600 hPa

· **Density At 20°C:** 0.788 g/cm³

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents: 78.6 %

Solids content: 20.0 %

· **Additional information:**

VOC (EU): 80.00 %

VOC (EU): 630.0 g/l

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Materials to be avoided:**

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 6)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 5)

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Prolonged or repeated contact with skin may cause slight irritation and/or reddening.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **Information about elimination (persistence and degradability):**
- **Other information:** There is no data available for the product.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10	packaging containing residues of or contaminated by dangerous substances
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04	gases in pressure containers (including halons) containing dangerous substances

(Contd. on page 7)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label** 2.1
- **Description of goods:** 1950 AEROSOLS
- **Limited quantities (LQ) LQ2**
- **Transport category** 2
- **Tunnel restriction code** D

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

* 15 Regulatory information

- **Chemical safety assessment** A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

Trade name: Dinitrol 8500 Lackgrundierer Grau AC Spray

(Contd. of page 7)

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	50-100

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R22 Harmful if swallowed.

R36 Irritating to eyes.

R36/37 Irritating to eyes and respiratory system.

R37/38 Irritating to respiratory system and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development

· **Contact:** Dr. Thomas Sürig

· *** Data compared to the previous version altered.**