

**Product: DINITROL VCI UNI O-40**

**Characteristics:** DINITROL VCI UNI O-40 is corrosion preventative oil with unique characteristics. It contains a VCI-inhibitor. In closed cavities the inhibitors are released, by vapour, over a long period of time. This is the perfect protection for fuel tanks, gearboxes and similar closed cavities.

DINITROL VCI UNI O-40 protects iron, steel, copper, brass and other metals without contact with the metal surface. Add 3-4 litres DINITROL VCI UNI O-40 to each m<sup>3</sup> air.

**Application:** DINITROL VCI UNI O-40 is an oil which is (concentrate) completely mixable with petrol, oil and diesel. It burns without leaving any ash. It is therefore not necessary to remove the DINITROL VCI UNI O-40, when starting up an engine.

**Removability:** DINITROL VCI UNI O-40 is removable with white spirit or alkali.

<b>TEST</b>	<b>VALUE</b>	<b>METHOD</b>
Density at 23°C	900-970 kg/m <sup>3</sup>	DIN 51757
Viscosity at 23°C, DIN 4	35-40 sec.	DIN 53211
Viscosity at 23°C	ca 250 cst	
Flash point	>55°C	

Health and safety information can be obtained from the material safety data sheet and the product label

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

EFTEC Aftermarket GmbH  
Pyrmonter Str. 76  
D-32676 Lügde

Telefon:  
+49 (0) 52 81 / 9 82 98-0

Telefax:  
+49 (0) 52 81 / 9 82 98-60